


# **WRANGLER 1708/2008**

## **Compact Automatic Scrubbers**



The Wrangler 1708 and Wrangler 2008 are the perfect compact automatic scrubbers. Designed to cover 10,000 to 20,000 square feet, these Wranglers are ideal for small office buildings, convenience stores, nursing homes and larger facilities with confined areas, such as grocery store checkout aisles, school cafeterias and kitchens, hotel lobbies, hospital rooms and reception areas.

Each Wrangler is available in either battery-powered or cord-electric models. The Wrangler 1708 features a 17-inch scrubbing path with a 10-gallon recovery tank and 8-gallon solution tank. The Wrangler 2008 has the same tank capacities with a 20-inch cleaning path. Both models feature rotocast polyethylene tank construction that's warranted for ten years.

The Wrangler 1708 and Wrangler 2008 feature breakaway squeegee assemblies. This safety feature prevents damage to the squeegee when it inadvertently catches on any fixed object. Instead of bending or breaking, the squeegee simply pulls away from the bracket at the rear of the machine. Reconnecting is as simple as hand tightening two control knobs.

**NSS Enterprises, Inc.**  
3115 Frenchmens Road  
Toledo, Ohio 43607-2958  
USA



# WRANGLER 1708/2008 Specifications

SCRUBBING PATH 1708 — 17 in. (43 cm) 2008 — 20 in. (51 cm)	FLOAT SHUT-OFF Ball type, easily detached for cleaning	DIMENSIONS Length 44.5 in. (113 cm) Width — 1708 19 in. (48 cm) Width — 2008 21.5 in. (55 cm) Body Height 30.5 in. (77.5 cm) Handle Height 40.5 in. (103 cm)
DRIVE Pad/brush assist	WHEELS/CASTERS Two 8 in. (20 cm) non-marking wheels. Two front 3 in. (7.6 cm) ball-bearing swivel casters w/extra strength stems	WEIGHT Machine Only Wrangler 1708 140 lbs. (63.5 kg) Wrangler 2008 141 lbs. (64 kg)
CLEANING RATE PER HOUR Unobstructed 8,231 ft. <sup>2</sup> (766 m <sup>2</sup> ) Obstructed 6,174 ft. <sup>2</sup> (574 m <sup>2</sup> )	CONSTRUCTION Rotocast polyethylene tanks/body, mounted on steel frame	SHIPPING WEIGHT Machine w/ batteries and charger Wrangler 1708 718 lbs. (328 kg) Wrangler 2008 719 lbs. (330 kg)
Unobstructed 9,684 ft. <sup>2</sup> (901 m <sup>2</sup> ) Obstructed 7,263 ft. <sup>2</sup> (676 m <sup>2</sup> )	TANK CAPACITIES Solution 8 gal. ( 30 l.) Recovery 10 gal. (38 l.)	WARRANTY 3 year limited 10 year poly parts
<i>Cleaning rates: Obstructed: Includes time for turnaround, tank empty/refill, operator variation and operation around obstacles. Unobstructed: Walking speed, with 2 in. (5 cm) overlap. Includes time for turnaround, tank empty/refill and operator variation.</i>	SQUEEGEE 32 in. (81 cm) swing type with breakaway feature; picks up in forward and reverse	
SOUND LEVEL 74 dbA		

BATTERY SPECIFICATIONS		ELECTRIC 120V. SPECIFICATIONS		ELECTRIC 240V. SPECIFICATIONS	
VACUUM MOTOR Type	2-stage, by-pass peripheral discharge	VACUUM MOTOR Type	2-stage, by-pass peripheral discharge	VACUUM MOTOR Type	2-stage, by-pass peripheral discharge
HP	.5 HP	HP	1.25 HP	HP	1 HP
CFM	65.1	CFM	92	CFM	95
CLOSED WATERLIFT	49 in. (124 cm)	CLOSED WATERLIFT	84 in. (213 cm)	CLOSED WATERLIFT	74 in. (188 cm)
POWER SUPPLY	Two 12V. 105 AH batteries	POWER SUPPLY	75 ft. (22.5 cm) 14-3 cord	POWER SUPPLY	75 ft. (22.5 cm) 1 mm cord
DRIVE MOTOR	Permanent magnet, 24V. DC .75 HP	DRIVE MOTOR	Permanent magnet, 120V. .75 HP	DRIVE MOTOR	Permanent magnet, 240V. .75 HP
BRUSH/PAD SPEED	200 RPM	BRUSH/PAD SPEED	250 RPM	BRUSH/PAD SPEED	250 RPM



By depressing a foot latch at the front of the machine, the operator can easily lift the body to gain access to batteries, pad driver and all internal components.

The ergonomic handles provide increased control of the machine's operation while also reducing operator fatigue.

The squeegee, which picks up in forward and reverse, swings wide on turns to recover all solution.



**NSS® Enterprises, Inc.**  
3115 Frenchmens Road  
Toledo, Ohio 43607-2958 USA  
419/531-2121 Fax 419/531-3761  
[www.nss.com](http://www.nss.com)  
[mailus@nss.com](mailto:mailus@nss.com)  
Specifications and appearance  
subject to change without notice.

DISTRIBUTED BY